



PRODUCT INFORMATION:

Nominal heat output: 6 kW
 Energy efficiency: 81 %
 CO%: 0,07 %

PRODUCT NUMBERS:

Product	Product number	Weight kg	Height mm
DEKO DUE C 1	703340-1	491	1200
DEKO DUE C 2	703340-2	442	1200
DEKO DUE C 3	703340-3	442	1200
DEKO DUE CB 1	703345-1	491	1200
DEKO DUE CB 2	703345-2	442	1200
DEKO DUE CB 3	703345-3	442	1200
DEKO DUE CL 1	703347-1	429	1200
DEKO DUE CL 2	703347-2	380	1200
DEKO DUE CL 3	703347-3	380	1200

ACCESSORIES:

Product	Product number	Weight kg	Height mm
Bottom plinth DC	707931	37	102
Floor protector DC white	920330		
Floor protector DC black	920332		

Product pictures are with accessories.

PRODUCT INFORMATION

	FIREWOOD		FLUE CALCULATION VALUES (1)				MAX. FLUE TEMPERATURE IN SECURITY TEST
	Length [cm]	Max amount of wood [kg/h]	Flue gas temperature [°C]	Min. flue draught [Pa]	Mass flow [g/s]	Flue connection Ø (min.)	Temperature °C
Deko Due C / CB / CL	25	1,65	255	-12	6,6	150	499

FLUE CONNECTION TABLE

	RECOMMENDED FLUE [mm]
	round Ø
Deko Due C / CB / CL	150

SAFETY DISTANCES TO COMBUSTIBLE MATERIALS

	CE-approval according to EN 13240		
	Behind	On the sides	Front
Deko Due C / CB	350	300	1100
Deko Due CL	70	300	1100

1) The flue calculation values apply for countries that require flue calculation in accordance with the DIN 18160 and DIN EN 13384 standards.

Take a notice of the countryspecific approvals in section 3

NOTES!

The recommended minimum flue height is 5 m. In countries where the flue calculation is required, should the calculation be done according to the instructions and regulations of the flue calculation.

A damper designed for adjusting the draft is always recommended for a flue connection or flue.

Country- and region-specific regulations must be adhered to when installing the fireplace

