




DEKO DUE S 1 + SL 1




DEKO DUE S 2 + SL 2




DEKO DUE S 3 + SL 3




DEKO DUE S 4 + SL 4




DEKO DUE SB 1



DEKO DUE SB 2



DEKO DUE SB 3



DEKO DUE SB 4

## PRODUCT INFORMATION:

Nominal heat output: 6 kW  
 Energy efficiency: 81 %  
 CO%: 0,07 %

## PRODUCT NUMBERS:

Product	Product number	Weight kg	Height mm
DEKO DUE S 1	703330-1	507	1200
DEKO DUE S 2	703330-2	475	1200
DEKO DUE S 3	703330-3	475	1200
DEKO DUE S 4	703330-4	508	1200
DEKO DUE SB 1	703335-1	507	1200
DEKO DUE SB 2	703335-2	475	1200
DEKO DUE SB 3	703335-3	475	1200
DEKO DUE SB 4	703335-4	508	1200
DEKO DUE SL 1	703337-1	429	1200
DEKO DUE SL 2	703337-2	397	1200
DEKO DUE SL 3	703337-3	397	1200
DEKO DUE SL 4	703337-4	430	1200

## ACCESSORIES:

Product	Product number	Weight kg	Height mm
Bottom plinth DS	707921	26	102
Floor protector DS/US white	920333		
Floor protector DS/US black	920331		

Product pictures are with accessories.

## PRODUCT INFORMATION

	FIREWOOD		FLUE CALCULATION VALUES (1)				MAX. FLUE TEMPERATURE IN SECURITY TEST
	Length [cm]	Max amount of wood [kg/h]	Flue gas temperature [°C]	Min. flue draught [Pa]	Mass flow [g/s]	Flue connection Ø (min.)	Temperature °C
Deko Due S / SB / SL	25	1,65	255	-12	6,6	150	499

## FLUE CONNECTION TABLE

	RECOMMENDED FLUE [mm]
	round Ø
Deko Due S / SB / SL	150

## SAFETY DISTANCES TO COMBUSTIBLE MATERIALS

	CE-approval according to EN 13240		
	Behind	On the sides	Front
Deko Due S / SB	350	300	1100
Deko Due SL	70	300	1100

1) The flue calculation values apply for countries that require flue calculation in accordance with the DIN 18160 and DIN EN 13384 standards.

Take a notice of the countryspecific approvals in section 3

### NOTES!

The recommended minimum flue height is 5 m. In countries where the flue calculation is required, should the calculation be done according to the instructions and regulations of the flue calculation.

A damper designed for adjusting the draft is always recommended for a flue connection or flue.

Country- and region-specific regulations must be adhered to when installing the fireplace

